SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
UK REACH Regulations (SI 2019/758 as amended)

Revision date 12/06/2024 **Revision Number** 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s) 2859,3009,3224,3241,3285,3286,3318,3465,3466,3467,3628

Product Name Tru-Tension - Snow Foam Aerosols

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cleaning agent

1.3. Details of the supplier of the safety data sheet

Manufacturer

Tru Tension Ltd
Sugnall Business Centre
Sugnall
Stafford
ST21 6NF
tel: +44 (0) 1275 792114

For further information, please contact;

Emergency Telephone Tel: +44 (0) 1275 792114 (Hours 09:00 - 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 2 - (H319)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Signal word
Danger

Hazard statements

H319 - Causes serious eye irritation
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
EUH208 Contains 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Precautionary statements
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection/ face protection
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	EC No (EU Index No)	UK REACH registration number	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7	1-5%	() 270-704-2	-	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-
Sodium Benzoate 532-32-1	1-5%	208-534-8	-	Eye Irrit. 2 (H319)	-	-	-
Propan-2-ol 67-63-0	1-5%	(603-117-00-0) 200-661-7	-	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)	-	-	-
1-methoxy-2-propanol 107-98-2	1-5%	(603-064-00-3) 203-539-1	-	Flam. Liq. 3 (H226) STOT SE 3 (H336)	-	-	-
Sodium lauroyl sarcosinate 137-16-6	<1%	205-281-5	-	Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	-	-	-
2-methyl-2H-isothiazol-3-one 2682-20-4	<1%	(613-326-00-9) 220-239-6	-	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.0015%	10	1

				(EUH071)			

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >= 0.1% (UK REACH Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	United Kingdom
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7	TWA: 1000 ppm TWA: 1750 mg/m³ STEL: 1250 ppm STEL: 2180 mg/m³
Propan-2-ol 67-63-0	TWA: 400 ppm TWA: 999 mg/m³ STEL: 500 ppm STEL: 1250 mg/m³
1-methoxy-2-propanol 107-98-2	TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³ Sk*

Biological occupational exposure limits This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Derived No Effect Level (DNEL) - Workers No information available

Chemical name	Oral	Dermal	Inhalation
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7		23.4 mg/kg bw/day [4] [6]	
Sodium Benzoate 532-32-1		62.5 mg/kg bw/day [4] [6]	3 mg/m³ [4] [6] 0.1 mg/m³ [5] [6]
Propan-2-ol 67-63-0		888 mg/kg bw/day [4] [6]	500 mg/m³ [4] [6]
1-methoxy-2-propanol 107-98-2		183 mg/kg bw/day [4] [6]	369 mg/m³ [4] [6] 553.5 mg/m³ [4] [7] 553.5 mg/m³ [5] [7]
Sodium lauroyl sarcosinate 137-16-6		20 mg/kg bw/day [4] [6]	70.53 mg/m³ [4] [6]
2-methyl-2H-isothiazol-3-one 2682-20-4			0.021 mg/m³ [5] [6] 0.043 mg/m³ [5] [7]

Derived No Effect Level (DNEL) - General Public No information available.

Chemical name	Oral	Dermal	Inhalation
Sodium Benzoate 532-32-1	16.6 mg/kg bw/day [4] [6]		1.5 mg/m³ [4] [6] 0.06 mg/m³ [5] [6]
Propan-2-ol 67-63-0	26 mg/kg bw/day [4] [6]		89 mg/m³ [4] [6]
1-methoxy-2-propanol 107-98-2	33 mg/kg bw/day [4] [6]		43.9 mg/m³ [4] [6]
Sodium lauroyl sarcosinate 137-16-6	10 mg/kg bw/day [4] [6]		17.39 mg/m³ [4] [6]
2-methyl-2H-isothiazol-3-one 2682-20-4	0.027 mg/kg bw/day [4] [6] 0.053 mg/kg bw/day [4] [7]		0.021 mg/m³ [5] [6] 0.043 mg/m³ [5] [7]

Predicted No Effect Concentration (PNEC) No information available.

Chemical name	Freshwater	Freshwater (intermittent release)	Marine water	Marine water (intermittent release)	Air
Sodium Benzoate 532-32-1	0.13 mg/L	305 µg/L	0.013 mg/L		
Propan-2-ol 67-63-0	140.9 mg/L	140.9 mg/L	140.9 mg/L		
1-methoxy-2-propanol 107-98-2	10 mg/L	100 mg/L	1 mg/L		
Sodium lauroyl sarcosinate 137-16-6	0.00891 mg/L	0.0891 mg/L	0.000891 mg/L	0.00891 mg/L	
2-methyl-2H-isothiazol-3-one 2682-20-4	3.39 µg/L	3.39 µg/L	3.39 µg/L	3.39 µg/L	

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
Sodium Benzoate 532-32-1	1.76 mg/kg sediment dw	0.176 mg/kg sediment dw	10 mg/L	0.06 mg/kg soil dw	300 mg/kg food
Propan-2-ol 67-63-0	552 mg/kg sediment dw	552 mg/kg sediment dw	2251 mg/L	28 mg/kg soil dw	160 mg/kg food
1-methoxy-2-propanol 107-98-2	52.3 mg/kg sediment dw	5.2 mg/kg sediment dw	100 mg/L	4.59 mg/kg soil dw	
Sodium lauroyl sarcosinate 137-16-6	0.0642 mg/kg sediment dw	0.0064 mg/kg sediment dw	3 mg/L	0.0076 mg/kg soil dw	
2-methyl-2H-isothiazol-3-one 2682-20-4			0.23 mg/L	0.0471 mg/kg soil dw	

8.2. Exposure controls

Engineering controls No information available.

Personal protective equipment

Eye/face protection	Tight sealing safety goggles. Safety glasses with side shields are recommended for medical or industrial exposures.
Hand protection	Impervious gloves. Wear suitable gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Aerosol
Colour	clear
Odour	Slight.

Property	**Values**	**Remarks • Method**
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	-41 - 117	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	13.1	
Lower flammability or explosive limits	1.8	
Flash point	-40	None known
Autoignition temperature	270	None known
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	Soluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	0.958	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size		
Particle Size Distribution		
Explosive properties	No information available	
Oxidising properties	No information available	

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	86,932.70 mg/kg
ATEmix (dermal)	185,243.80 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-dust/mist)	99,999.0000 mg/l
ATEmix (inhalation-vapour)	957.90 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Sodium Benzoate	= 4070 mg/kg (Rat)	-	-
Propan-2-ol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	> 10000 ppm (Rat) 6 h
1-methoxy-2-propanol	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat) 6 h
Sodium lauroyl sarcosinate	-	-	0.5175 (Rat) 4 h
2-methyl-2H-isothiazol-3-one	232 - 249 mg/kg (Rat) = 120 mg/kg (Rat)	= 200 mg/kg (Rabbit)	= 0.11 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Sodium Benzoate	-	LC50: 420 - 558mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas)	-	EC50: <650mg/L (48h, Daphnia magna)
Propan-2-ol	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)
1-methoxy-2-propanol	-	LC50: =20.8g/L (96h, Pimephales promelas)	-	EC50: =23300mg/L (48h, Daphnia magna)
Sodium lauroyl sarcosinate	-	LC50: =107mg/L (96h, Danio rerio)	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	<=2.8
Sodium Benzoate	-2.13
Propan-2-ol	0.05
1-methoxy-2-propanol	<1
2-methyl-2H-isothiazol-3-one	-0.26

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	The substance is not PBT / vPvB
Sodium Benzoate	The substance is not PBT / vPvB
Propan-2-ol	The substance is not PBT / vPvB
1-methoxy-2-propanol	The substance is not PBT / vPvB
Sodium lauroyl sarcosinate	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, Flammable, 2.1
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	A145, A167, A802
ERG Code	10L

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	63,190, 277, 327, 344, 381, 959
EmS-No.	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	

RID

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5F

ADR

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1

14.5 Environmental hazards No
14.6 Special precautions for user
Special Provisions 190, 327, 344, 625
Classification code 5F
Tunnel restriction code (E)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Authorisations and/or restrictions on use:
This product does not contain substances subject to authorisation (UK REACH - Annex XIV). This product does not contain substances subject to restriction (UK REACH - Annex XVII).

Persistent Organic Pollutants
Not applicable

Export Notification requirements
Not applicable

Dangerous substance category per COMAH (SI 2015/483 as amended)
P3a - FLAMMABLE AEROSOLS
P3b - FLAMMABLE AEROSOLS

Named dangerous substances per COMAH (SI 2015/483 as amended)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE - 68476-85-7	50	200

The Ozone-Depleting Substances Regulations 2015
Not applicable

The Biocidal Products Regulations 2001 (as amended)

Chemical name	The Biocidal Products Regulations 2001 (as amended)
Sodium Benzoate - 532-32-1	Cat A
2-methyl-2H-isothiazol-3-one - 2682-20-4	PT6 PT11 PT12 PT13

The Water Environment (Water Framework Directive) (England and Wales) Regulations 2017 (as amended)
Not applicable

Poisons and Explosive Precursors
Not applicable

International Inventories
TSCA See inventories below
DSL/NDSL See inventories below
EINECS/ELINCS See inventories below
ENCS See inventories below
IECSC See inventories below
KECI See inventories below
PICCS See inventories below

AIIC	See inventories below
NZIoC	See inventories below

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals

15.2. Chemical safety assessment

Chemical Safety Report No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3
H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H336 - May cause drowsiness or dizziness
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Legend
SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
+	Sensitisers		

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method

Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS
Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine’s PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 12/06/2024

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)
Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

UK SDS version information - XGHS
UL release:
GHS Revision 7
2022 Q1

United Kingdom Full process, including GHS and Transportation Wizards

Full text of H-Statements referred to under section 3	H225 - Highly flammable liquid and vapour H226 - Flammable liquid and vapour H301 - Toxic if swallowed H311 - Toxic in contact with skin H314 - Causes severe skin burns and eye damage H315 - Causes skin irritation H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H319 - Causes serious eye irritation H330 - Fatal if inhaled H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life H410 - Very toxic to aquatic life with long lasting effects

Chemical name	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	Flam. Gas 1 (H220) Press. Gas (H280)	
Sodium Benzoate	Eye Irrit. 2 (H319)	
Propan-2-ol	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)	
1-methoxy-2-propanol	Flam. Liq. 3 (H226) STOT SE 3 (H336)	
Sodium lauroyl sarcosinate	Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	
2-methyl-2H-isothiazol-3-one	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Sens. 1A :: C>=0.0015%